MATERIAL SAFETY DATA SHEET

	1. Product and Company Identification		
Product number	6204		
Product name	Penetrating Lubricant		
Effective date	13-Jun-2012		
Company information	IXL Premium Lubricants, Inc		
	Roy, Utah 84067 United States		
Company phone	General Assistance 1-800-872-4951		
Emergency telephone US	1-866-836-8855		
Emergency telephone outside US	1-952-852-4646		
Version # 01			
	2. Hazards Identification		
Emergency overview	Aerosol. FLAMMABLE CONTENTS UNDER PRESSURE. Irritating to eyes. Prolonged exposure may cause chronic effects.		
Potential health effects			
Routes of exposure	Skin contact. Eye contact. Ingestion.		
Eyes	Contact with eyes may cause irritation.		
Skin	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.		
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.		
Ingestion	Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.		
Target organs	Central nervous system. Lungs.		
Chronic effects	May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.		
Signs and symptoms	Discomfort in the chest. Narcosis. Coughing. Defatting of the skin. Skin irritation.		
2	. Composition / Information on Ingredients		

Components	CAS #	Percent
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	30 - 40
Propane	74-98-6	8 - 10
Odorless Mineral Spirits	64742-48-9	8 - 10
Non-hazardous and other components below reportable levels		40 - 60

4. First Aid Measures		
First aid procedures		
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.	
Skin contact	Take off immediately all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops and persists.	
Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.	
Ingestion	If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not induce vomiting without advice from poison control center. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	

	5	5. Fire Fighting Mea	asures	
Flammable properties Protection of firefighters	Runoff to	sewer may cause fire o	r explosion hazard.	
Specific hazards arising the chemical				
	Protective equipment and In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.			
	6. A	ccidental Release	Measures	
Methods for containment	Stop the	flow of material, if this is	without risk.	
Methods for cleaning up		ills: Wipe up with absorb y to remove residual cor	pent material (e.g. cloth, fleen ntamination.	ece). Clean surface
		7. Handling and St	orage	
Handling	or until sp defective eyes. We	prayed surface is thoroug Do not re-use empty co ar personal protective e	ghly dry. Do not use if spra ontainers. Avoid contact wit quipment. Avoid prolonged	h skin. Avoid contact with exposure.
Storage	Keep away from heat and sources of ignition. Store in cool place. Keep away from food, drink and animal feedingstuffs. Level 2 Aerosol.			
	8. Exposı	ire Controls / Perse	onal Protection	
Exposure limits				
ACGIH				
Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
OSHA				
Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Personal protective equipme	nt			
Eye / face protection		goggles are recommen	ded	
Skin protection			ant clothing. Chemical resi	stant gloves.
Respiratory protection		-	-	-
	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.			
	mechanic		cartridge or an air-supplied	
Appearance	mechanic 9. Ph	al filter / organic vapor c	cartridge or an air-supplied	
••	mechanic 9. Ph Compres	al filter / organic vapor o	cartridge or an air-supplied	
Boiling point	mechanic 9. Ph Compres	al filter / organic vapor o ysical & Chemical sed liquefied gas.	cartridge or an air-supplied	
Boiling point Color	9. Ph Compres 197.6 °F Yellow.	al filter / organic vapor o ysical & Chemical sed liquefied gas.	cartridge or an air-supplied	
Boiling point Color Density	9. Ph Compres 197.6 °F Yellow. 0.8789 g/	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated	cartridge or an air-supplied	
Boiling point Color Density Flammability (HOC)	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated	cartridge or an air-supplied	
Boiling point Color Density Flammability (HOC) Flash back Flash point	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (-	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated	cartridge or an air-supplied	
Boiling point Boiling point Color Density Flammability (HOC) Flash back Flash point Form	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (- Aerosol.	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated 104.4 °C) Propellant	cartridge or an air-supplied	
Boiling point Color Density Flammability (HOC) Flash back Flash point Form Freezing point	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (- Aerosol. Not availa	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated 104.4 °C) Propellant	cartridge or an air-supplied	
Boiling point Boiling point Color Density Flammability (HOC) Flash back Flash point Form Freezing point Ddor	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (- Aerosol. Not availa Oily.	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated 104.4 °C) Propellant able	cartridge or an air-supplied	
Boiling point Color Density Flammability (HOC) Flash back Flash point Form Freezing point Odor pH	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (- Aerosol. Not availa Oily. Not applie	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated 104.4 °C) Propellant able	cartridge or an air-supplied	
Boiling point Color Density Flammability (HOC) Flash back Flash point Form Freezing point Odor pH Physical state	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (- Aerosol. Not availa Oily. Not applie Liquid.	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated 104.4 °C) Propellant able cable	cartridge or an air-supplied	
Appearance Boiling point Color Density Flammability (HOC) Flash back Flash point Form Freezing point Odor pH Physical state Pressure	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (- Aerosol. Not availa Oily. Not applie Liquid. 45 - 65 ps	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated 104.4 °C) Propellant able	cartridge or an air-supplied	
Boiling point Color Density Flammability (HOC) Flash back Flash point Form Freezing point Odor pH Physical state	9. Ph Compres 197.6 °F Yellow. 0.8789 g/ 27.44 kJ/ Yes -156 °F (- Aerosol. Not availa Oily. Not applie Liquid.	al filter / organic vapor o ysical & Chemical sed liquefied gas. (92.2 °C) estimated cm3 estimated g estimated 104.4 °C) Propellant able cable sig @ 70F	cartridge or an air-supplied	

Product name: Penetrating Lubricant

Product #: 652-000 Revision date: 13-JUN-2012 Print date: 13-JUN-2012

10. Chemical Stability & Reactivity Information

Chemical stability Conditions to avoid Risk of ignition.

Conditions to avoidHeat, flames and sparks. Aerosol containers are unstable at temperatures above 49°C.Hazardous decomposition productsNo hazardous decomposition products are known.

11. Toxicological Information

Component analysis - LD50 Toxicology Data - Selected LD50s and LC50s Odorless Mineral Spirits 64742-48-9 Ora

Odorless Mineral Spirits	64742-48-9
Propane	74-98-6
Synthetic Isoparaffinic	64742-47-8
Hydrocarbon	

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >3160 mg/kg Inhalation LC50 Rat 658 mg/L 4 h Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

12. Ecological Information

Ecotoxicity

Waste codes

Disposal instructions

Contains a substance which causes risk of hazardous effects to the environment.

13. Disposal Considerations

D001: Waste Flammable material with a flash point <140 F
Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Aerosols
2.1
UN1950
153, N82
LTD QTY
None
None
Until 12/3



Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking but not concurrently.

IMDG

Basic shipping requirements:	
Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	None



ΙΑΤΑ

Basic shipping requirements:	
Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



	1:	5. Regulatory Information		
US federal regulations	Standard,	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. CERCLA/SARA Hazardous Substances - Not applicable.		
Occupational Safety and Health A	dministration	n (OSHA)		
29 CFR 1910.1200 hazardous chemical	Yes	Yes		
CERCLA (Superfund) reportable q	uantity			
lone				
Superfund Amendments and Rear	uthorization A	Act of 1986 (SARA)		
Section 302 extremely hazardous substance	No			
Section 311 hazardous chemi	cal Yes			
Hazard categories (311/312)	Delayed H Fire Haza Pressure	e Hazard - Yes Hazard - Yes ard - Yes Hazard - Yes / Hazard - No		
nventory status				
Country(s) or region	Inventory nar	me	On inventory (yes/no)	
China	Inventory of E	xisting Chemical Substances in China (IECSC)	N	
Europe	European Inve	entory of New and Existing Chemicals (EINECS)	N	
Europe	European List	of Notified Chemical Substances (ELINCS)	N	
Japan	Inventory of E	xisting and New Chemical Substances (ENCS)	N	
Korea			N	
United States & Puerto Rico	Toxic Substan	nces Control Act (TSCA) Inventory	Ye	
A "Yes" indicates that all componen	ts of this produc	ct comply with the inventory requirements administered by t	the governing country(s)	
state regulations				
U.S Pennsylvania - RTK (Right	to Know) List			
Odorless Mineral Spirits	64742-48-9	Present		
Propane Synthetic Isoparaffinic Hydrocarbon	74-98-6 64742-47-8	Present Present		
		16. Other Information		
urther information	HMIS® is	a registered trade and service mark of the NPCA.		
HMIS® ratings	Health: 1' Flammab Physical I	* ility: 3		
isclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information gived designed only as a guidance for safe handling, use, processing, storage, transported disposal and release and is not to be considered a warranty or quality specification. Information relates only to the specific material designated and may not be valid for safe in the text. The information in the sheet was written based on the best knowledge an experience currently available.			. The information given is g, storage, transportation, r quality specification. The d may not be valid for such y process, unless specified	
Prepared by	-	ry Compliance		

Product name: Penetrating Lubricant Product #: 652-000 Revision date: 13-JUN-2012 Print date: 13-JUN-2012