

Material Safety Data Sheet



Ambassador IXL Manufacturing, Inc.

Section 1. Chemical Product and Company Identification

Product Name	<i>IXL™ Premium Diesel Treatment</i>	
Supplier	Ambassador IXL Manufacturing, Inc 1930 West 3350 South Roy, Utah 84057 1-800-872-4951	
Material Uses	Diesel Fuel Additive	
National Fire Protection Association (U.S.A.)		

Section 2. Composition and Information on Ingredients

Name	CAS #	% by Weight
2-Ethylhexyl Nitrate	27247-96-7	30.0 - 60.0
Ethylene Glycol Monobutyl Ether	111-76-2	10.0 - 30.0
Solvent Naphtha, Petroleum, Light Arom	64742-95-6	10.0 - 30.0
1,2,4-Trimethylbenzene	95-63-6	< 10.0
Naphtha, Hydrotreated Heavy	64742-48-9	< 5.0
Xylene	1330-20-7	< 2.0
Trimethylbenzene	25551-13-7	< 2.0
Ethylbenzene	100-41-4	< 0.5
Vinyl Acetate Monomer	108-05-4	< 0.1

(See Section 8 for exposure guidelines)
 (See Section 15 for regulatory information)

SARA 311 Categories:
 Immediate (Acute) Health Effects.....: Yes
 Delayed (Chronic) Health Effects.....: Yes
 Fire Hazard.....: Yes
 Sudden Release Of Pressure Hazard....: No
 Reactivity Hazard.....: Yes

Section 3. Hazard Identification

EMERGENCY OVERVIEW

Flammable liquid. Keep away from sparks and open flames. When heated above 100 Deg C, may undergo an exothermic reaction which causes a rapid rise in temperature and pressure. Rupture of storage vessels and fire should be anticipated in case of such temperature. Can cause severe lung damage and may be fatal if swallowed. May cause central nervous system depression.

HMIS Rating

Health: 2

Flammability: 2

Reactivity: 1

NFPA Rating

Health: 2

Flammability: 2

Reactivity: 1

POTENTIAL HEALTH EFFECTS

EYE:

May cause eye irritation or discomfort.

SKIN:

Harmful if absorbed through the skin. Prolonged or repeated contact may result in drying of the skin which may result in skin irritation and dermatitis.

INHALATION:

Vapor inhalation and/or skin absorption can cause central nervous system effects, including dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Chronic exposures may cause hearing loss, irregular heart rhythms and potential cardiac arrest.

Moderately irritating to respiratory tract.

INGESTION:

Liquid can directly enter the lungs when swallowed or vomited. Serious lung damage and possibly fatal chemical pneumonia can develop if this occurs.

SIGNS AND SYMPTOMS OF EXPOSURE:

Effects of overexposure may include eye and skin irritation, irritation of the nose and throat. Central nervous system effects include dizziness, headache, drowsiness, loss of coordination, fatigue, giddiness, loss of appetite and abdominal pain. Symptoms of ingestion include irritation of digestive tract, nausea, vomiting and diarrhea.

CARCINOGENICITY INFORMATION:

Vinyl Acetate Monomer has been classified by the International Agency for Research on Cancer as possibly carcinogenic to humans (Group 2B). This IARC classification was based upon limited evidence of carcinogenicity to animals and inadequate evidence of carcinogenicity to humans.

Ethylbenzene has been classified by IARC as a possible human carcinogen (Group 2B) on the basis of sufficient evidence of carcinogenicity in experimental animals, but inadequate evidence in exposed humans.

TARGET ORGAN:

Target organs: Heart, Auditory System.

Section 4. First Aid Measures

EYE CONTACT FIRST AID:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses if worn. Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:

Wash skin with plenty of soap and water while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.

INHALATION FIRST AID:

Remove to fresh air.

If not breathing, give artificial respiration and contact a physician immediately. If breathing is difficult, administer oxygen and contact a physician immediately.

INGESTION FIRST AID:

If swallowed, do NOT induce vomiting, but have the victim rinse mouth with water, and then drink 2 - 4 cupfuls of water. Get immediate medical attention. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

NOTES TO PHYSICIAN:

Activated charcoal mixture may be administered. To prepare activated charcoal mixture, suspend 50 grams activated charcoal in 400 mls of water and mix thoroughly. Administer 5 ml/kg or 350 ml for an average adult. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk justified by the presence of additional toxic substances. Activated charcoal may induce vomiting, but may be given after emesis or lavage to absorb toxic additives. Steroid therapy in mild to moderate cases does not improve outcome. Bacterial pneumonia often occurs after exposure, but prophylactic antibiotics are not indicated and should be reserved for documented bacterial pneumonia.

Light hydrocarbons have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhanced these effects.

Section 5. Fire Fighting Measures

FLAMMABLE PROPERTIES

PMCC Flash Point: 46.1 C (115.0 F)

Autoignition Temperature: N/A

FLAMMABLE LIMITS IN AIR

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA:

Dry chemical, water spray (fog), carbon dioxide, foam.

FIRE & EXPLOSION HAZARDS:

Flammable Liquid. Vapors will burn releasing toxic vapors, fumes and smoke, including carbon monoxide and organic vapors. Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture or explosion.

FIRE FIGHTING INSTRUCTIONS:

As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

Avoid breathing smoke and vapor.

When heated above 100 Deg C, may undergo a self-accelerating, exothermic reaction which causes a rapid rise in temperature and pressure. Rupture of storage vessels and fire should be anticipated in case of such temperatures. Spray storage vessels with water to maintain temperature below 100 Deg C.

COMBUSTION PRODUCTS:

Hazardous decomposition products are oxides of carbon and nitrogen including CO and CO₂.

Section 6. Accidental Release Measures

SAFEGUARDS (PERSONNEL):

Wear appropriate personal protective equipment (See Section 8). Evacuate non-emergency personnel to a safe area.

If applicable, report spills to the proper environmental agencies as required by federal, state and local regulations.

INITIAL CONTAINMENT:

Eliminate all sources of ignition - Heat, sparks, flame, electricity, and impact. Contain spilled material with dikes or absorbents. Marine Pollutant. Do not allow material to enter soil, surface water, or sewer system.

LARGE SPILLS PROCEDURE:

Stop the source of the leak, if it is safe to do so. Contain spilled

material. Vacuum or sweep up material and place in a disposal container. Absorb residue with inert material (e.g. dry sand or earth), then place in a chemical waste container. Do not flush to sewer. Use explosion-proof equipment during clean-up.

SMALL SPILLS PROCEDURE:

Absorb spills with inert material. Transfer to a chemical waste container and dispose of properly. Spills are extremely slippery and should be cleaned up immediately.

MISCELLANEOUS:

Treat or dispose of in accordance with all federal, state, and local requirements.

Section 7. Handling and Storage

HANDLING (PERSONNEL): DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Ground and bond containers when transferring material.

Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Keep away from food and drinking water.

HANDLING (PHYSICAL ASPECTS):

Secure container after each use. Store in a cool dry, secure area. Keep out of reach of children. Ground containers when transferring material.

Avoid contact with strong oxidizing agents.

Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner, or properly disposed of.

STORAGE PRECAUTIONS:

Store in a tightly closed container. Store in a cool dry place. Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction. Contact with hot surfaces may ignite the product.

Section 8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS:

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

EYE / FACE PROTECTION REQUIREMENTS:

Wear safety glasses with side shields (or goggles) and a face shield.

SKIN PROTECTION REQUIREMENTS:

Wear protective gloves to minimize skin contamination. When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

Wash hands thoroughly after handling.

RESPIRATORY PROTECTION REQUIREMENTS:

Under normal use conditions, with adequate ventilation, no special handling equipment is required. If anticipating close contact with this product or its mist, local ventilation may be required to keep exposure below limits.

EXPOSURE GUIDELINES:

ETHYLENE GLYCOL MONOBUTYL ETHER

OSHA PEL: 25 ppm, 120 mg/m³

OSHA TWA: 25 ppm

ACGIH TWA: 25 ppm

1,2,4-TRIMETHYLBENZENE

ACGIH TWA: 25 ppm

XYLENE

OSHA TWA: 100 ppm

ACGIH TWA: 100 ppm

OSHA STEL: 150 ppm

ACGIH STEL: 150 ppm

TRIMETHYLBENZENE

OSHA TWA: 25 ppm

ACGIH TWA: 25 ppm

ETHYLBENZENE

OSHA TWA: 100 ppm

OSHA STEL: 125 ppm

ACGIH STEL: 125 ppm

Section 9. Physical and Chemical Properties

FORM: Liquid

COLOR: Amber

ODOR: Aromatic hydrocarbon

SOLUBILITY IN WATER ...: Nil

SPECIFIC GRAVITY: 0.923 at 60 Deg F (Water = 1)

BULK DENSITY: 7.69 Pounds per Gallon at 60 Deg F

PH: Not applicable

Section 10. Stability and Reactivity

STABILITY:

Stable at normal temperatures and storage conditions.

POLYMERIZATION:

Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Avoid contact with strong oxidizing agents, such as nitric and sulfuric acids, halogens, hydrogen peroxide and chlorinating agents. May burn or react violently with fluorine/oxygen mixtures with 50-100% fluorine. Decomposes with heat.

DECOMPOSITION:

In the case of fire, a complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide, smoke and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

CONDITIONS TO AVOID:

Sources of ignition and temperatures above 50C (122F) - 60C (140F).

Section 11. Toxicological Information

EYE EFFECTS:

Solvent Petroleum Naphtha, slightly irritating (rabbit).

Vinyl Acetate Monomer is a severe eye irritant (rabbit).

SKIN EFFECTS:

Solvent Petroleum Naphtha, no deaths reported at 4 ml/kg (Rat). Slightly irritating (rabbit, 4 hour(s)).

2-Ethylhexyl Nitrate is harmful in contact with skin.

Vinyl Acetate Monomer, Skin absorption LD50 is 2,335 mg/kg in rabbits.

ACUTE ORAL EFFECTS:

Solvent Petroleum Naphtha, LD50, 10 ml/kg in rats.

Naphthalene, Oral LD50, 2600 mg/kg (rat).

Ethylene Glycol Monobutyl Ether, Oral LD50, 1.4 g/kg (Guinea Pig).

Oral LD 50 for Vinyl Acetate Monomer is 2,920 mg/kg in rats.

ACUTE INHALATION EFFECTS:

Solvent Petroleum Naphtha, no deaths at 710 ppm (v) (Rat) 4 Hour (s).

Vinyl Acetate Monomer, four hour inhalation LC50 is 4,000 ppm in rats.

MISCELLANEOUS:

Please contact supplier for additional toxicological information.

Section 12. Ecological Information

ENVIRONMENTAL HAZARDS:

Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.

MISCELLANEOUS:

Ecotoxicity: Ingredient Name:

2-Ethylhexyl Nitrate:

Trout	24 Hours	145 mg/l
Trout	48 Hours	116 mg/l

Bluegill	96 Hours	4.5 mg/l
Bluegill	48 Hours	6 mg/l
Bluegill	72 Hours	5.4 mg/l.

Section 13. Disposal Considerations

WASTE DISPOSAL:

Do not dispose of into waste water treatment facilities. Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

This material, if discarded, is considered a hazardous waste under RCRA Regulation 40 CFR 161.

Section 14. Transportation Information

PRODUCT LABEL: MM WT XL Plus Concentrate
 D.O.T. SHIPPING NAME: Flammable Liquid, n.o.s
 TECHNICAL SHIPPING NAME ...: Contains Petroleum Naphtha, 2-Ethylhexylnitrate
 D.O.T. HAZARD CLASS: 3
 UN NUMBER: UN1993
 D.O.T. PLACARD: Flammable Liquid
 PACKAGE CLASS: Packing Group III

MISCELLANEOUS:

This material is a marine pollutant when shipped in quantities greater than 119 gallons.

This material is not regulated for US DOT transportation in quantities less than 119 Gallons.

Section 15. Regulatory Information

REGULATORY DISCLOSURES:

New Jersey Right to Know list:

1,2,4-Trimethylbenzene, CAS #95-63-6, < 10.0 %.

Xylene, CAS # 1330-20-7, < 2.0 %.

Pennsylvania Right to Know List:

1,2,4-Trimethylbenzene, CAS #95-63-6, < 10.0 %.

Xylene, CAS # 1330-20-7, < 2.0 %.

Ethylbenzene, CAS # 100-41-4, < 0.5 %.

Ethylene Glycol Monobutyl Ether, CAS # 111-76-2, 10 - 30 %.

Canadian Disclosure List

ETHYLENE GLYCOL MONOBUTYL ETHER (111-76-2)

1,2,4-TRIMETHYLBENZENE (95-63-6)
TRIMETHYLBENZENE (25551-13-7)
ETHYLBENZENE (100-41-4)

SARA Title III - Section 313

1,2,4-TRIMETHYLBENZENE (95-63-6)
XYLENE (1330-20-7)

CERCLA Hazardous Substances

XYLENE (1330-20-7) -- RQ 1000 lb
ETHYLBENZENE (100-41-4) -- RQ 1000 lb
VINYL ACETATE MONOMER (108-05-4) -- RQ 5000 lb

RCRA Hazardous Substances

XYLENE (1330-20-7) -- RCRA Code: U239

Clean Air Act - Section 112

VINYL ACETATE MONOMER (108-05-4)

Title V

1,2,4-TRIMETHYLBENZENE (95-63-6)
XYLENE (1330-20-7)
ETHYLBENZENE (100-41-4)
VINYL ACETATE MONOMER (108-05-4)

SC Toxic Air Pollutants List

XYLENE (1330-20-7)
ETHYLBENZENE (100-41-4)
VINYL ACETATE MONOMER (108-05-4)

MISCELLANEOUS INFORMATION:

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

Section 16. Other Information

NOTE: The information on this MSDS is based on data which is considered to be accurate. Ambassador IXL Manufacturing, Inc., however, makes no guarantees or warranty, either expressed or implied of the accuracy or completeness of this information.

The conditions or methods of handling, storage, use and disposal of the products are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This MSDS was prepared and is to be used for this product. If the product is used as a component in another product, this MSDS information may not be applicable.